Optimation OptiLogic
SKU: KWP-OPTLG0-PRD

Product Overview

The Optimation OptiLogic driver works in conjunction with KEPServerEX to exchange data between OPC clients and OptiLogic Ethernet RTUs using the UDP protocol. KEPServerEX automatically optimizes data acquisition based on client demand and ensures data integrity through extensive error handling.

Features

- Supports 4 Slot RTU Base
- Covers all I/O modules supported by the OptiLogic RTU
- Supports Digital I/O and Analog I/O
- Supports serial ports modules and base serial port operation
- Supports all Operator Panels
- Automatic Tag Database Generation
- High-speed operation designed for SoftPLC I/O
- Supports all data types

Protocols

- OptiLogic

Supported Devices

- OL2108 - Supported Module
- OL2109 - Supported Module
- OL2111 - Supported Module
- OL2201 - Supported Module
- OL2208 - Supported Module
- OL2211 - Supported Module
- OL2252 - Supported Module
- OL2408 - Supported Module
- OL2418 - Supported Module
- OL3406 - Supported Module
- OL3420 - Supported Module
- OL3440 - Supported Module
- OL3850 - Supported Module
- OL4054 - Supported RTU
- OL4058 - Supported RTU

Application Support

- OPC Data Access (OPC DA) Versions 1.0a, 2.0, 2.05a, and 3.0
- OPC Alarms and Events (OPC AE) Version 1.10
- OPC Unified Architecture (OPC UA) Version 1.01
- OPC .NET Service (OPC .NET) Version 1.00
- SuiteLink and FastDDE for Wonderware
- NIO Interface for iFIX
- DDE Format CF_Text and AdvancedDDE

Featured Suites

- Manufacturing Suite