Uni-Telway
SKU: KWP-TLMUW0-PRD

Product Overview

The Telemecanique Uni-Telway driver works in conjunction with KEPServerEX to exchange data between OPC clients and Telemecanique Unitelway protocol compliant PLCs. KEPServerEX automatically optimizes data acquisition based on client demand and ensures data integrity through extensive error handling.

Features

- Supports Uni-Telway RS-485 Multi-drop
- Supports any Uni-Telway compatible device
- Supports the following Memory Types: MB, MW, KW, T.P, T.V, T.Q, C.P, C.V, and C.D
- Supports all data types
- Modem Support
    - Automatic dial configuration
    - Multiple phone number management

Protocols

- Uni-Telway

Supported Devices

- TSX 07
- TSX 17
- TSX 37
- TSX 47
- TSX 57
- Small Frame
- Large Frame

Application Support

- OPC Data Access (OPC DA) Versions 1.0a, 2.0, 2.05a, and 3.0
- OPC Alarms and Events (OPC AE) Version 1.10
- OPC Unified Architecture (OPC UA) Version 1.01
- OPC .NET Service (OPC .NET) Version 1.00
- SuiteLink and FastDDE for Wonderware
- NIO Interface for iFIX
- DDE Format CF_Text and AdvancedDDE

Additional Tech Info

- Devices that do not support the full 128-byte data field provided by the Uni-Telway protocol are considered "Small Frame."

Featured Suites

- Manufacturing Suite